

社内管理入系文番
文番番号 EV578-A
保管場所
GT2品証

Material Safety Data Sheet

Date prepared : May 18 2005
 Date revised : May 18 2005
 Document identifier : 20050518040900-6

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name : HM-403(ASAHIMELT S140)
 Company Name : ASAHI CHEMICAL SYNTHETIC CO.,LTD.
 Section in its duty : Sales Department
 Address : 2-18-10 NAKACHOU TODA-SHI SAITAMA JAPAN
 Phone : 048-441-5625(JAPAN)
 FAX : 048-441-5645(JAPAN)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Composition : Mixture
 Chemical name : Ethylene-vinyl acetate copolymer-based hot melt adhesives
 Synonyms : EVA-based HMA
 Main ingredient name and content :

100%.such as an Ethylene-vinyl acetate copolymer etc

UN Classification. UN Dangerous Goods Number :

It doesn't correspond to dangerous articles in the UN definition

3. HAZARDS IDENTIFICATION

This product has no hazardous ingredients

Eye contact : Dust/power may irritate eye tissue.
 Rubbing may cause abrasion of the cornea.
 Symptoms may include irritation, redness, scratching of the cornea, and tearing.

Skin contact : Prolonged or repeated skin contact may cause imitation.
 Hot/molten product may cause thermal burns.

Inhalation : Inhalation of dusts may cause respiratory irritation.
 Inhalation of vapor/fumes from molten product may cause respiratory irritation with throat discomfort, Coughing and difficulty breathing.
 Inhalation of vapors/fumes from molten product may cause congestion of respiratory, dizziness and nausea.

Ingestion : Ingestion of small amounts is not expected to produce adverse health effects.
 Ingestion of large quantities may result in gastrointestinal disturbances including irritation, nausea, and diarrhea.

4. FIRST-AID MEASSURES

Eye contact : When hot / molten product goes into an eye.cool with water immediately and get medical attention.

- Skin contact : In case of skin contact wash immediately with soap and water. If hot / molten product contacts skin. Cool under running water. Do not attempt to remove the hot / molten or cooled product from the skin. Get medical attention.
- Inhalation : In the case of inhalation of vapors/fumes from molten product. remove to fresh air immediately, and keep at rest, and get medical attention if necessary.
- Ingestion : If swallowed, contact a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical Personnel.

5. FIRE-FIGHTING MEASURES

- Extinguishing media : Dry chemical powder, CO₂, foam.
In case of large fires, foam should be used.
- Fire fighting : Keep personnel removed and windward of fire, wearing self-contained breathing apparatus or proper eyes and skin protector.
- Formation gases in fire : CO, CO₂ and other toxic gases as thermal decomposition products

6. ACCIDENTAL RELEASE MEASURES

When hot / molten product leak out, put on protective equipment (see section 8). remove source of fire and prevent from entering drains, ensure adequate ventilation, and them remove off after cooling.

7. HANDLING AND STORAGE

Avoid breathing fumes if product is used high temperatures.
Handle with protective gloves, long sleeve clothes, safety glasses.
Keep away from fire when handling and storage.
Store in a tightly closed container and in the dark.
Guard against dust and water accumulation of this product.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Ventilation : Provide local exhaust and general ventilation systems.
- Protective glasses : Required.
- Eye protection : Required.(safety glasses, face protection)
- Protective clothes : Long sleeve clothes, safety shoes etc.
- Work/hygienic practice : Safety showers and eye-wash fountains.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state and Appearance : Milk-white Solid
- R&B Softening point : 75°C
- Specific gravity : 0.7-1.3 at 23°C(Water=1)
- Solubility (water) : Insoluble in water.
- Flash point : >210°C
- Inflammability : Yes

1 0 . STABILITY AND REACTIVITY

- Stability : Stable at normal temperature and Pressure
Reactivity : At the temperature exceeding near 200°C. polymerization or decomposition is promoted and the rising viscosity, gelling, etc. are caused.

1 1 . TOXICOLOGICAL INFORMATION

No data

1 2 . ECOLOGICAL INFORMATION

No data

1 3 . DISPOSAL CONSIDERATIONS

Disposal should be in accordance with any local state or national regulations.
Incineration under approved incinerator is the preferred method.

1 4 . TRANSPORT INFORMATION

Transport should be in accordance with any local state or national regulations.
Dangerous good of IMO (sea transport) and ICAO (air transport)
It doesn't correspond to dangerous articles in the UN definition

1 5 . REGULATORY INFORMATION

Any existing national regulations for handling of "Ethylene-vinyl acetate copolymer-based hot melt adhesives" must be observed.

1 6 . OTHER INFORMATION

The data here is based on our current knowledge and experience.
The data can be revised by new information.
The purpose of this Safety Data Sheet is to describe the products from the point of view of safety requirements.
Therefore it should not be construed as guaranteeing specific properties.

Asahi Chemical Synthetic CO.,LTD
Osaka Office Supervisor

Masahiro Kijima

18.05.2005

Asahi Chemical Synthetic CO., Ltd.

HM-403 (ASAHIMELT S140) Material Compositions

1. HM-403 (ASAHIMELT S140) is a hot melt adhesive and the material compositions are listed on the Existing Chemistry Substance Name List.

Official Gazette Public Announcement Reference Number

6 - 6	EVA
CAS No.	24937-78-8
6-1031	Adhesion grant agent resin
CAS No.	68132-00-3
8-414	Wax
CAS No.	63231-60-7
3-1693	Prevention of oxidization agent
CAS No.	6683-19-8

2. There is no use of organic solvent or specific chemistry substance (Cadmium, Lead, Mercury) PCB, Phenol, Formaldehyde when producing HM-403 (ASAHIMELT S140).

Asahi Chemical Synthetic CO., LTD
Osaka Office Supervisor

Masahiro Kijima