


# MATERIAL SAFETY DATA SHEET

| SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION   |               |   |           |                           |                                     |
|--|---------------|---|-----------|---------------------------|-------------------------------------|
| <b>PRODUCT NAME:</b> Mitsubishi SLM - A C Activator  |               | <b>DATE:</b> December 16, 2008  |           |                           |                                     |
| <b>PRODUCT NUMBER:</b>   |               | <b>DATE PREPARED:</b> December 16, 2008   |           |                           |                                     |
| TRADE NAME: Mitsubishi SLM - A C Activator<br>GENERAL USE: Activator Concentrate for SLM/SDP<br>PRODUCT DESCRIPTION: Colorless corrosive liquid, amine odor.   |               |   |           |                           |                                     |
| <b>MANUFACTURER</b><br>Mitsubishi Imaging (MPM), Inc.  |               | <b>SUPERSEDES:</b> October 20, 2007   |           |                           |                                     |
| <b>ADDRESS (NUMBER, STREET, P.O. BOX)</b><br>555 Theodore Fremd Avenue   |               | <b>TELEPHONE NUMBER FOR INFORMATION / Customer Service</b><br>(914) 925-3200  |           |                           |                                     |
| <b>(CITY, STATE AND ZIP CODE)</b><br>Rye, NY 10580   |               | <b>CHEMTREC 24-HOUR EMERGENCY TELEPHONE NUMBER</b><br>1-800-424-9300      01-703-527-3887<br>North America Toll Free      International |           |                           |                                     |
| <b>COUNTRY</b><br>USA  |               |   |           |                           |                                     |
| SECTION 2 - HAZARDOUS INGREDIENTS  |               |   |           |                           |                                     |
| Hazardous Components   | % (by Weight) | CAS #   | EINECS #  | Hazard Symbol             | RISK PHRASES (Full Text Section 15) |
| Sodium Hydroxide (a,b)   | 1 - 5         | 1310-73-2   | 215-185-5 | C                         | R-35                                |
| Potassium Hydroxide (a,b)  | 1 - 5         | 1310-58-3   | 215-181-3 | C                         | R-35                                |
| n-Aminoethyl Ethanolamine  | 1 - 5         | 111-41-1  | 203-867-5 | C                         | R-21/22, 34, 43                     |
| (a) See Section 15   |               |   |           |                           |                                     |
| (b) A "C" in the OSHA PEL or ACGIH TWA column indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.   |               |   |           |                           |                                     |
| <b>NOTES:</b> Note: This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 91/155/EEC. Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European (GHS) directive 91/155/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directive 67/548/EEC. |               |   |           |                           |                                     |
| SECTION 3 - HAZARDS IDENTIFICATION   |               |   |           |                           |                                     |
| <b>EMERGENCY OVERVIEW</b>  |               |   |           |                           |                                     |
| Corrosive alkaline liquid, moderately toxic, contact with eyes may cause severe irritation or chemical burns, contact with skin may cause irritation. Ingestion may cause gastric distress and chemical burns to the digestive tract.<br>Hazard symbols for this product - <b>C</b> . Risk Phrases - <b>R 34, 36/37/38</b>   |               |   |           |                           |                                     |
| <b>POTENTIAL HEALTH EFFECTS</b>  |               |   |           |                           |                                     |
| <b>INHALATION:</b><br>Corrosive and irritating to upper respiratory tract and mucous membranes.  |               |   |           |                           |                                     |
| <b>SKIN:</b><br>Corrosive and irritating; chemical burns may result from contact; severe irritant.   |               |   |           |                           |                                     |
| <b>EYES:</b><br><b>CORROSIVE;</b> Contact with eyes is painful and irritating and will cause chemical burns.   |               |   |           |                           |                                     |
| <b>INGESTION:</b><br>Corrosive and irritating to digestive tract; may cause gastric distress, stomach pains and vomiting.  |               |   |           |                           |                                     |
| <b>CARCINOGENICITY:</b>  |               |   |           |                           |                                     |
| NTP? <b>NO</b>   |               | IARC MONOGRAPHS? <b>NO</b>  |           | OSHA REGULATED? <b>NO</b> |                                     |
| CALIFORNIA, Prop.65? <b>NO</b>   |               |   |           | ESIS NOTATION? <b>NO</b>  |                                     |
| SECTION 4 - FIRST AID MEASURES   |               |   |           |                           |                                     |
| <b>INHALATION:</b><br>Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.  |               |   |           |                           |                                     |
| <b>EYES:</b><br>Remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention immediately.  |               |   |           |                           |                                     |
| <b>SKIN:</b><br>Wash contacted area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention.  |               |   |           |                           |                                     |
| <b>INGESTION:</b><br>Drink large quantities of water or milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately.   |               |   |           |                           |                                     |

# MATERIAL SAFETY DATA SHEET

**PRODUCT NAME:** Mitsubishi SLM - A C Activator  
**PRODUCT NUMBER:** \_\_\_\_\_ **DATE:** December 16, 2008

## SECTION 5 - FIRE FIGHTING MEASURES

**GENERAL HAZARDS:**  
 Product is corrosive. Products of combustion include compounds of carbon, hydrogen, nitrogen and oxygen, including Carbon Monoxide.

**EXTINGUISHING MEDIA:**  
 Carbon Dioxide, water, water fog, dry chemical, chemical foam.

**FIRE FIGHTING PROCEDURES:**  
 Keep containers cool with water spray to prevent container rupture due to steam buildup; **CAUTION** - material is corrosive.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**  
 None

**HAZARDOUS COMBUSTION PRODUCTS:**  
 Smoke, fumes, oxides of carbon, oxides of nitrogen

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**  
**CAUTION - CORROSIVE.** Wash small spills to sanitary sewer. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container for disposal. For spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements.

## SECTION 7 - HANDLING AND STORAGE

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**  
 Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Separate from oxidizing materials, metallic powders and other easily oxidized organic materials and reducing agents. **CAUTION** - material is corrosive. Keep this and other chemicals out of reach of children.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

| HAZARDOUS COMPONENTS             | NIOSH   |           |          |            | ACGIH       |           | OSHA     |            |
|----------------------------------|---------|-----------|----------|------------|-------------|-----------|----------|------------|
|                                  | TWA ppm | TWA mg/m3 | STEL ppm | STEL mg/m3 | TLV/TWA ppm | TWA mg/m3 | STEL ppm | STEL mg/m3 |
| <b>Sodium Hydroxide (a,b)</b>    |         | <b>2C</b> | —        | —          |             | <b>2C</b> | —        | —          |
| <b>Potassium Hydroxide (a,b)</b> |         | <b>2C</b> |          | —          |             | <b>2C</b> |          | —          |
| <b>n-Aminoethyl Ethanolamine</b> |         | <b>NE</b> |          |            |             | <b>NE</b> |          |            |

**(b) A "C" in the OSHA PEL or ACGIH TWA column indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.**

### PERSONAL PROTECTION

**RESPIRATORY PROTECTION:**  
 None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

**PROTECTIVE GLOVES:**  
 Neoprene or rubber gloves with cuffs.

**EYE PROTECTION:**  
 Protective eyeglasses or chemical safety goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**  
 Coveralls, apron, or other equipment should be worn to minimize skin contact.

**WORK / HYGIENIC PRACTICES:**  
 Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

|   |  |
|---|--|
| <b>APPEARANCE AND ODOR</b><br>Colorless liquid, amine odor. | <b>VAPOR PRESSURE</b><br>17 mm Hg @ 20° C            |
| pH<br>14.0 ± 0.2  | <b>SPECIFIC GRAVITY (WATER = 1)</b><br>1.106 ± 0.005 |
| <b>BOILING POINT / BOILING RANGE</b><br>212° F (100° C)     | <b>SOLUBILITY IN WATER</b><br>Complete               |
| <b>FLASH POINT</b><br>Non-Flammable                         | <b>VISCOSITY</b><br>Not Specified                    |
| <b>FLAMMABLE LIMITS</b><br>LEL: NA UEL: NA                  | <b>VAPOR DENSITY (AIR = 1)</b><br>> 1                |
| <b>AUTO-IGNITION TEMPERATURE</b><br>ND                      | <b>EVAPORATION RATE (WATER = 1)</b><br>< 1           |

**VOLATILE ORGANIC COMPOUND (VOC) INFORMATION**  
 There are no known Volatile Organic Compounds (VOCs) in this product.

# MATERIAL SAFETY DATA SHEET

**PRODUCT NAME:** Mitsubishi SLM - A C Activator  
**PRODUCT NUMBER:** \_\_\_\_\_ **DATE:** December 16, 2008

## SECTION 10 - STABILITY AND REACTIVITY

**STABILITY**                      STABLE                      X                      **CONDITIONS TO AVOID:**  
**Extreme temperatures.**

**INCOMPATIBILITY (MATERIALS TO AVOID):**  
**Strong oxidizers, strong acids, strong alkalis.**

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:**  
**Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.**

**HAZARDOUS POLYMERIZATION:** Will Not Occur.                      **CONDITIONS TO AVOID:**  
**None Related to Polymerization.**

## SECTION 11 - TOXICOLOGICAL INFORMATION

| Hazardous Components             | CAS #<br>EINECS # | LD50 of Ingredient<br>(Specify Species and Route) | LC50 of Ingredient<br>(Specify Species) |
|----------------------------------|-------------------|---|---|
| <b>Sodium Hydroxide (a,b)</b>    | <b>1310-73-2</b>  | <b>40 mg / kg<br/>IPR - Mouse</b>                 | <b>NE</b>                               |
|                                  | <b>215-185-5</b>  |   |   |
| <b>Potassium Hydroxide (a,b)</b> | <b>1310-58-3</b>  | <b>273 mg / kg<br/>Oral - rat</b>                 | <b>NE</b>                               |
|                                  | <b>215-181-3</b>  |   |   |
| <b>n-Aminoethyl Ethanolamine</b> | <b>111-41-1</b>   | <b>3000 mg / kg<br/>Oral - rat</b>                | <b>NE</b>                               |
|                                  | <b>203-867-5</b>  |   |   |

Do not allow undiluted and/or large quantities of product to enter sewage systems or reach ground water or bodies of water.

## SECTION 12 - ECOLOGICAL INFORMATION


No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

## SECTION 13 - DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHOD:**  
 According to the European Waste Catalogue, waste codes are application specific and should be assigned by the user based on the application for which the product is used. Dispose of in accordance with Local, State, and Federal Regulations. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for corrosive materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

## SECTION 14 - TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** **Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide, Potassium Hydroxide), UN 3266**

|   |   |
|---|---|
| DOT HAZARD CLASS / Pack Group: <b>8 / III</b><br>REFERENCE: <b>49 CFR 173.154, .203, .241</b><br>UN / NA IDENTIFICATION NUMBER: <b>UN 3266</b><br>LABEL: <b>CORROSIVE</b><br>HAZARD SYMBOLS: <div style="text-align: center; margin-top: 10px;">  </div> | IATA HAZARD CLASS / Pack Group: <b>8 / III</b><br>IMDG HAZARD CLASS: <b>8 / III</b><br>RID/ADR Dangerous Goods Code: <b>8</b><br>UN TDG Class / Pack Group: <b>8 / III</b><br>Hazard Identification Number (HIN): <b>80</b> |
|---|---|

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

