

SYSTEM # 2

BESELER

2016-MTB-III / TD-16-10 SYSTEM



Easy access slide out control panel



Standard Digital Temp Control



New heavy duty magnetic hold down



Easy access slide out control panel



Storage shelf and casters are standard



Micro perforator standard

System Features

- 20" x 16" seal area
- Self-adjusting seal pads
- Easy quick change Mono seal wire
- Fully welded seal head
- Fully welded 11 gauge steel frame
- Heavy duty magnetic holddown
- Auto seal temp compensator
- Variable speed soft start conveyor
- Stainless steel film hold downs
- Quick lock wire tensioners
- E Z access control panel
- 24 Pin Micro perforator
- Storage shelf and Casters
- 16" wide 10" tall 28" long tunnel chamber
- Digital P.I.D. temperature control
- Automatic cool down circuit
- No maintenance mesh belt
- Adjustable top and side air damper
- High velocity/volume blower
- Heat ducted to all sides, top and bottom
- Variable speed 0-60 fpm conveyor
- E Z access slide out control panel
- Durable electro-static powder finish
- 4000 watts of available heat
- Casters included
- ONE YEAR WARRANTY (including seal wire)

MODEL	MACHINE SIZE L x W x H	SHIPPING SIZE/ WEIGHT	POWER REQUIRED	SEAL AREA TUNNEL AREA	PACKAGES PER MINUTE	MAXIMUM PRODUCT SIZE
2016- MTB-II L-SEALER	56" x 30" x 35"	73" x 48" x 59" 350 lbs	115 VOLTS 15 AMPS	20" x 16" L x W	15-18	19" x 15" L x W
TD-16-10 TUNNEL	33" x 26" x 26"	48" x 52" x 59" 300 lbs	220VOLTS 1PH 25 AMPS	16"x 10"x28" W x H x L	15-18	15" x 9" W x H

BESELER SHRINK PACKAGING

1560 NW BLVD VINELAND, NJ 08360 • PHONE (800) 678-8324 • FAX (856) 765-1663